

Energy Efficiency Design Summary

(Part 9 Residential)

This form is used to summarize the energy efficiency design of the project. Information on completing this form is on the reverse

For use by Principal Authority	
Application No:	Model/Certification Number

A. Project Information

Building number, street name		Unit number	Lot/Con
Municipality	Postal code	Reg. Plan number / other description	

B. Compliance Option

<input type="checkbox"/> <i>SB-12 Prescriptive</i> [SB-12 - 2.1.1.]	Table: Package: A B C D E F G H I J K L M (circle one)
<input type="checkbox"/> <i>SB-12 Performance*</i> [SB-12 - 2.1.2.]	* Attach energy performance calculations using an approved software
<input type="checkbox"/> <i>Energy Star®*</i> [SB-12 - 2.1.3.]	* Attach BOP form
<input type="checkbox"/> <i>EnerGuide 80®*</i>	* House must be evaluated by NRCan advisor and meet a rating of 80

C. Project Design Conditions

Climatic Zone (SB-1):	Heating Equipment Efficiency	Space Heating Fuel Source
<input type="checkbox"/> Zone 1 (< 5000 degree days)	<input type="checkbox"/> ≥ 90% AFUE	<input type="checkbox"/> Gas <input type="checkbox"/> Propane <input type="checkbox"/> Solid Fuel
<input type="checkbox"/> Zone 2 (≥ 5000 degree days)	<input type="checkbox"/> ≥ 78% < 90% AFUE	<input type="checkbox"/> Oil <input type="checkbox"/> Electric <input type="checkbox"/> Earth Energy
Windows+Skylights+Glass Doors		Other Building Conditions
Gross Wall Area =	% Windows+ _____ %	<input type="checkbox"/> ICF Basement <input type="checkbox"/> Walkout Basement <input type="checkbox"/> Log/Post&Beam
Gross Window+ Area =		<input type="checkbox"/> ICF Above Grade <input type="checkbox"/> Slab-on-ground

D. Building Specifications [provide values and ratings of the energy efficiency components proposed, or attach *Energy Star* BOP form]

Building Component	RSI / R values	Building Component	Efficiency Ratings
Thermal Insulation		Windows & Doors¹	
Ceiling with Attic Space		Windows/Sliding Glass Doors	
Ceiling without Attic Space		Skylights	
Exposed Floor		Mechanicals	
Walls Above Grade		Space Heating Equip. ²	
Basement Walls		HRV Efficiency (%)	
Slab (all >600mm below grade)		DHW Heater (EF)	
Slab (edge only ≤600mm below grade)		NOTES 1. Provide U-Value in W/m2.K, or ER rating 2. Provide AFUE or indicate if condensing type combined system used	
Slab (all ≤600mm below grade, or heated)			

E. Performance Design Verification [complete applicable sections if *SB-12 Performance*, *Energy Star* or *EnerGuide80* options used]

SB-12 Performance:
 The annual energy consumption using Subsection 2.1.1. SB-12 Package _____ is _____ Gj (1 Gj =1000Mj)
 The annual energy consumption of this house as designed is _____ Gj
 The software used to simulate the annual energy use of the building is: _____
 The building is being designed using an air leakage of _____ air changes per hour @50Pa.

Energy Star. BOP form attached. The house will be labeled on completion by:

Energy Star and *EnerGuide80*:
 Evaluator/Advisor/Rater Name: _____ Evaluator/Advisor/Rater Licence #: _____

F. Designers [names of designers who are responsible for the building code design and whose plans accompany the permit application]

Architectural	Mechanical
---------------	------------

Guide to the Energy Efficiency Design Summary Form

The *Energy Efficiency Design Summary* form summarizes the compliance path used by a house designer to comply with energy efficiency requirements of the Ontario Building Code. This form must accompany the building permit application. The information on this form MUST reflect the drawings and specifications being submitted, or the building permit may be refused. Refer to Supplementary Standard SB-12 for details about building code compliance requirements. Further information about energy efficiency requirements for new buildings is available from the provincial building code website at www.mah.gov.on.ca, or the municipal building department.

Beginning January 1, 2012, a house designer must use one of four energy efficiency compliance options in the building code:

1. Comply with the *SB-12 Prescriptive* design tables,
2. Use the *SB-12 Performance* compliance method, and model the design against the prescriptive standards,
3. Design to *Energy Star* standards, or
4. Evaluate the design according to *EnerGuide* technical procedures and achieve a rating of 80 or more.

COMPLETING THE FORM

B. Compliance Options

Indicate the compliance option being used.

- *SB-12 Prescriptive* requires that the building conforms to a package of thermal insulation, window and mechanical system efficiency requirements set out in Subsection 2.1.1. of SB-12. Energy efficiency design modeling and testing of the building is not required under this option.
- *SB-12 Performance* refers to the alternative method of compliance set out in Subsection 2.1.2. of SB-12. Using this approach the designer must use recognized energy simulation software (such as HOT2000 V9.34c1.2 or newer), and submit documents which show that the annual energy use of the building is equal to a prescriptive package.
- *Energy Star* houses must be designed to *Energy Star* requirements and be labelled on completion by Enerquality or other agency. The *Energy Star* BOP form must be submitted with the permit documents.
- *EnerGuide80* houses are validated by NRCan authorized energy advisors and must achieve a rating of 80 or more when evaluated in accordance with *EnerGuide* administrative and technical procedures.

C. Project Design Conditions

Climatic Zone: The number of degree days for Ontario cities is contained in Supplementary Standard SB-1

Windows, Skylights and Glass Doors: If the ratio of the total gross area of windows, sidelights, skylights and glass doors to the total gross area of walls is more than 17%, higher efficiency glazing is required. If the ratio is more than 22% the *SB-12 Prescriptive* option may not be used. The total area is the sum of all the structural rough openings. Some exceptions apply. Refer to 2.1.1.1. of SB-12 for further details.

Fuel Source and Heating Equipment Efficiency: The fuel source and efficiency of the proposed heating equipment must be specified in order to determine which *SB-12 Prescriptive* compliance package table applies.

Other Building Conditions: These construction conditions affect *SB-12 Prescriptive* compliance requirements.

D. Building Specifications

Thermal Insulation: Indicate the RSI or R-value being proposed where they apply to the house design. Under the *SB-12 Prescriptive* option, RSI 3.52 wall insulation is permitted in certain conditions where other design elements meet higher standards. Refer to SB-12 for further details.

E. Performance Design Summary

This section is not required to be completed if the *SB-12 Prescriptive* option is being used.

AIRTIGHTNESS REQUIREMENTS FOR NEW HOUSES

All houses must comply with increased air barrier requirements in the building code. Notice of air barrier completion must be provided and an inspection conducted prior to it being covered. A blower door test to verify the air tightness of the house must be conducted during construction if the *NRCan EnerGuide80* option is used, or if the *SB-12 Performance* or *Energy Star* options are used and an air tightness of less than 2.5 ACH @ 50 Pa in the case of detached houses, or 3.0 ACH @ 50 Pa in the case of attached houses is necessary to meet the required energy efficiency standard.

ENERGY EFFICIENCY LABELING FOR NEW HOUSES

Energy Star and *EnerGuide* issue labels for new homes constructed under their energy efficiency programs. The building code does not regulate new home labelling.